

BITUMEN REMOVER GEL

Efficient remover for removing old Tectyl® residue, bitumen and other oil and wax emulsion based products



Product description

Bitumen Remover Gel is a mild and effective product for the removal of old Tectyl® residue, anti-rust coatings and bitumen. Bitumen Remover Gel is a highly concentrated mixture of surfactants and dissolves the most stubborn wax and oil based products.

Bitumen Remover Gel is completely biodegradable.

Use

Bitumen Remover Gel can be applied on almost all porous and non-porous surfaces such as metal, plastics, concrete, masonry and natural stone. Common surfaces are trains, subways, street furniture and buildings.

Characteristics

- Quickly and effectively removes the most stubborn old Tectyl® residue, anti-rust coatings and bitumen.
- Suitable for many surfaces
- Powerful dissolving power
- Completely biodegradable
- Suitable for both indoor and outdoor use

Technical data

Odour:	Odorless
Colour:	Transparent
Specific weight:	0,87 kg/L
pH:	~ 7-8
Contains:	Surfactants
Flash point:	-100°C

Application conditions

Bitumen Remover Gel can be used in all dry weather conditions.

Instructions

1. Apply Bitumen Remover Gel with a brush.
2. Let the product dwell 30 minutes up to 5 hours on the pollution.
3. Jet of the graffiti using high pressure (80-150 bar) and hot water (~70-90°C). Pressure depends on the surface.
4. Optional: in the case of graffiti based on Tectyl® residues, apply an anti-graffiti coating immediately after removing the graffiti.

Packaging

5 L

Consumption

Take into account a consumption of 5 - 10 m²/L surfaces and 5 - 15 m²/L on non-porous surfaces. Consumption always depends on the surface and the graffiti.

Practical information

- Do not dilute or mix with other products, be careful with acidic products.
- Low temperature can decrease the efficiency, adjust the dwelling time accordingly.
- Do not use in direct sunlight or on hot surfaces.
- Clean tools and product residues with clean water.
- For application on hard, non-porous surfaces, the liquid Bitumen Remover is more effective.

Storage

Can be stored in original unopened packaging for at least 24 months. Store in a dry, cool and frost-free place.

Health and safety

Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. When in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680
E. info@mavro-int.com
W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: February 2022
All previous editions become invalid upon this publication

Product code: 57624