

GRAFFITI REMOVER GEL

Powerful, universal graffiti remover



Product description

Graffiti Remover Gel is our most used and universally suitable graffiti remover. It is a carefully formulated mixture of solvents and additives for optimal removal.

Graffiti Remover Gel dissolves and cleans almost all types of graffiti and inks without damaging the underlying surface. Graffiti Remover Gel is a gel-like product and is therefore very suitable for use on vertical surfaces while minimising product waste.

Use

Graffiti Remover Gel is highly suitable for removing graffiti from hard, porous surfaces such as granite, natural stone, marble, lime stone, concrete, slate, masonry, bricks and inorganic paints. Graffiti Remover Gel can also be used on hard, non-porous surfaces such as metal, glass, treated wood, tiles, ceramic and some types of plastic.

Characteristics

- Biodegradable
- Mild odour
- Removes graffiti quickly and thoroughly
- Suitable for use on almost any surface
- Highly suitable for removing graffiti from masonry, concrete and facades.

Technical data

Colour:	Green
Odour:	Characteristically mild
Specific weight:	1.20 kg/ L
pH:	8
Contains:	Solvents
Flashpoint:	~ 90°C

Application conditions

Graffiti Remover Gel can be used in all dry weather conditions.

Instructions

Graffiti removal from walls, concrete and other porous surfaces:

1. Cover floors using a suitable absorbent material such as Absorbent Rolls
2. Apply Graffiti Remover Gel undiluted to the surface using a chemical resistant brush.
3. Let the product dwell on the surface for 20 to 60 minutes and regularly agitate the graffiti using a brush.
4. Jet off the graffiti using high pressure (150 bar) and hot water (90°C). Pressure depends on the surface.
5. Optional: apply a permanent or semi-permanent anti-graffiti coating directly after removal of graffiti.

Graffiti removal from metal, glass and other hard, nonporous surfaces:

6. Apply a small amount of Graffiti Remover Gel on a dry microfiber cloth or power sponge.
7. Apply the product to the graffiti and allow to dwell for 5-15 minutes.
8. Wipe off the graffiti using a clean part of the cloth and rinse the surface with plenty clean water.

9. Optional: apply a permanent or semi-permanent anti-graffiti coating directly after removal of graffiti.

Packaging

1 and 10 L

Consumption

Take into account a consumption of 5 - 10 m²/L surfaces and 5 - 15 m²/ L on non-porous surfaces. Consumption always depends on the surface and the graffiti.

Practical information

- Do not dilute or mix with other products.
- Low temperature can decrease the efficiency, adjust the dwelling time accordingly.
- Do not use in direct sunlight or on hot surfaces.
- Clean tools and product residues with clean water.

Storage

Can be stored in original unopened packaging for at least 24 months. Store in a dry, cool and frost-free place.

Health and safety

Avoid skin and eye contact, wear suitable rubber gloves, protective clothing and safety goggles. When in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680
E. info@mavro-int.com
W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2020
All previous editions become invalid upon this publication

Product code: 57608