

INOXCOAT

High-quality transparent coating for the preservation of stainless steel



Product description

Inoxcoat is a high-quality, semi-permanent, transparent coating for the preservation of stainless steel.

Inoxcoat gives stainless steel surfaces a beautiful satin finish and prevents adhesion of dirt and grease. Innoxcoat is therefore the solution for fingerprints, stains and smudges that often occur on stainless steel.

Innoxcoat offers long-lasting protection with high abrasion and impact resistance.

Innoxcoat repairs minor scratches and makes weathered stainless steel surfaces like new.

Use

Innoxcoat can be used both indoors and outdoors on all stainless steel surfaces. Common applications are elevators, escalators, dispensers and sheeting. When used outdoors, the lifespan strongly depends on the weather conditions and location. Innoxcoat is widely used in offices, stations, airports, museums and many other applications.

Characteristics

- Waterborne
- Satin finish
- Easy application
- Easy maintenance and is easily removed with
- Innoxcoat REMOVER

Technical data

Odour:	Characteristically mild
Colour:	Yellow
Specific weight:	1,05 kg/L
pH:	~ 8

Application conditions

Innoxcoat can be applied in all dry weather conditions with temperatures between 8°C and 20°C. Do not apply in direct sunlight.

Instructions

1. Clean the surface thoroughly with Innox Pre-Clean. If necessary use a power sponge to aid in cleaning.
2. Degrease and dry the surface with Innox Degreaser.
3. Fold a microfiber cloth in half several times or wrap a microfiber cloth around a power sponge.
4. Apply a small amount of Innoxcoat on the microfiber cloth and apply Innoxcoat to the surface. Work in long lengths and always in the same direction to avoid streaks
5. If necessary, apply a second layer after 10-15 minutes. Streaking and/or missed areas will no longer be visible after a second later.
6. In case of errors in application, Innoxcoat can easily be repaired with Innoxcoat Remover.

Drying

10-15 minutes

Packaging

500 mL and 1 L

Consumption

75-125 m²/L

Practical information

- Work in areas of 1- 2 m² to avoid streaking and difference in layer thickness.
- Work in the direction of the surface (brush direction) to maintain a natural appearance.
- Do not mix or dilute with other products.

Storage

Can be kept for at least 12 months in original unopened packaging.

Store in a cool, frost-free place.

Health and safety

Avoid eye contact, wear safety goggles. If in doubt, always consult the safety data sheet or our R&D department.

Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel

T. +31 418 680 680

E. info@mavro-int.com

W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2020

All previous editions become invalid upon this publication

Product code: 57883