

LIME REMOVER

Powerful acid cleaner for removing limescale and cement residue

Product description

Lime Remover is an acidic cleaner based on hydrochloric acid for the removal of limescale, carbonates and contaminants caused by salt and soot deposits.

Use

Lime Remover is suitable for cleaning acid-resistant surfaces such as masonry, tiles, floors and glass.

Characteristics

- Efficient, fast cleaning
- Is friendly on most surfaces
- Can be used as a saline solution on concrete

Technical data

Odour: Mildly acidic Colour: Transparent Specific weight: 1,05 kg/L

ρΗ: ~1

Contains: Hydrochloric acid

Application conditions

Lime Remover can be used in all dry weather conditions.

Instructions

- 1. Apply Lime Remover undiluted with a brush.
- 2. Pour the product on horizontal parts and spread with a brush or broom
- Allow the product to work on the surface for 5-10 minutes.
 Keep the surface moist during the application time.
- 4. Rinse and clean the surface with a high-pressure cleaner. Depending on the surface, use a pressure between 50 and 200 bar. Use cold or warm water with a maximum temperature of 50 $^{\circ}$ C.
- Repeat the procedure if necessary.

Packaging

1, 5 and 10 L

Consumption

Consumption is 3-5 m2/L depending on nature and degree of the contamination and the porosity of the surface.

Practical information

- Do not dilute or mix with other products. Be careful with alkaline products.
- Low temperature can decrease the efficiency, adjust the dwelling time accordingly.
- Do not apply in direct sunlight or on hot surfaces.
- Do not allow the product to dry.
- When used indoors, ensure proper ventilation.
- Use Cementresidue Remover for extreme cases of white deposits.

Storage

Can be stored in original unopened packaging for at least 24 months. Store in a dry, well ventilated cool and frost-free place.

Health and safety

Causes severe burns and eye damage. Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. When in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel

T. +31 418 680 680 E. info@mavro-int.com W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2020

All previous editions become invalid upon this publication

Product code: 57603