

PEELABLE CLEANER

Durable spray film for cleaning surfaces where conventional cleaning agents, water or pressure are not possible



Product description

Peelable Cleaner is a 1-component, water-based coating based on a durable 100% recycled polymer emulsion. After drying, Peelable Cleaner forms a durable, transparent film which can easily be removed from the surface.

Peelable Cleaner has cleaning properties when applied in liquid form. The cleaning properties ensure that all contaminants of the substrate are loosened and absorbed in the coating. After drying, the film is removed from the substrate along with all contaminants.

Peelable Cleaner removes dust, soot and other surface contaminations.

Peelable Cleaner is completely UV- and frost-resistant after drying.

Use

Peelable Cleaner can be used on virtually all porous substrates such as marble, sandstone, limestone, travertine, gypsum, terracotta and masonry and concrete.

Peelable Cleaner has been specially developed for cleaning where traditional liquid cleaners cannot be used safely or where rinsing with water/pressure can be impractical. Examples are monumental buildings, gymnasiums with wooden floors and buildings with fire damage.

Characteristics

- Fully UV-resistant
- Solvent-free
- Forms a transparent layer
- Can be removed without leaving a residue
- Increased viscosity for application in one coat to most surfaces
- Cleaning effect
- Requires no rinsing or scrubbing

Technical data

Colour:	White
Odour:	Odorless
Specific gravity:	Approx. 1.03 kg/liter
pH:	Approx. 9-10

Application conditions

Ambient temperature:	maximum 30°C, minimum 10°C
Substrate temperature:	max. 30°C, minimal 10°C
Relative air humidity:	max. 85%

Instructions

1. Cover parts not to be treated, such as (ventilation) vents, guides and sun blinds with tape.
2. Apply Peelable Cleaner by means of an airless or HVLP paint sprayer. Total minimum consumption is 0.5 - 0.8 kg/m². In case of strongly porous substrates or substrates with a rough structure, a high layer thickness is of great importance.
3. Attention: Applying too little layer thickness can cause major problems during the removal of the coating.
4. Peelable Cleaner can also be applied with a block brush or long-haired roller.

5. Remove Peelable Cleaner by gently pulling the coating away from the substrate at an angle.

Drying

Cured: 24-48 hours depending on conditions and layer thickness

Package

1, 5 and 10 kg

Consumption

0,6 - 0,8 kg/m² depending on the surface.

Practical information

- Do not dilute or mix with other products.
- Clean equipment after use with an alkaline cleaner
- Always apply a test beforehand to make sure the substrate is suitable.
- Airless spray application 100 to 150 bar and 0.015 - 0.019 inch spray tip. Please contact our technical advisors for advice.
- Coating is dry when transparent.
- Do not use on wood or painted surfaces.
- Peelable Cleaner dries in contact with air, precautions should be taken during the application of the coating to prevent partially dried material. Always close the container tightly during and after use.

Storage

In original, tightly closed and unopened packaging, can be stored for at least 6 months. Store in a cool, frost-free place.

Health & safety

Wear suitable gloves and safety goggles. Always wear a dust mask to prevent inhalation of spray mist. If in doubt, always consult the safety data sheet or our R&D department.

Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel

T. +31 418 680 680

E. info@mavro-int.com

W. www.mavro-int.com



Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: January 2022

All previous editions become invalid upon this publication

Product code: 57668