

TEGELPROTECT

High-quality nano-coating for making bathroom tiles and other stone surfaces water- and dirt-repellent



Product description

Tegelprotect forms an invisible water and dirt-repellent layer on the surfaces and makes this easy to clean.

Tegelprotect is easy to apply and can be used both indoor and outdoor.

Use

Tegelprotect has been specially developed for application on light porous mineral surfaces such as bathroom tiles, exposed concrete, terracotta tiles, tile grout, glazed tiles and natural stone.

Characteristics

- Easy application
- Waterborne thus no odour
- Reduces the adhesion of dirt
- Protect the surface from limescale
- Excellent water-, dirt- and grease-repellent properties

Technical data

| | |
|------------------|----------------------------|
| Odour: | Odourless |
| Colour: | Transparent |
| Specific weight: | 1,0 kg/L |
| pH: | ~5 |
| Contains: | Silanes and fluoropolymers |

Application conditions

| | |
|------------------------|----------------------------|
| Ambient temperature: | maximum 30°C, minimum 10°C |
| Substrate temperature: | maximum 30°C, minimum 10°C |
| Relative humidity: | maximum 85% |

Instructions

1. Ensure that the surface is clean, dry and dust-free.
2. Apply Tegelprotect evenly with a paint roller.
3. Ensure that the surface is properly saturated. Apply a second layer wet-on-wet with a maximum of 30 minutes between the layers.
4. Prevent oversaturation by removing any excess product with a clean cloth.

Drying

| | |
|------------|--------------------------|
| Dust-free: | 30 minutes up to an hour |
| Dry: | After 2 – 4 hours |

Packaging

500 mL

Consumption

Consumption is 5 m²/L

Practical information

- Do not mix or dilute with other products.
- Use Glasprotect for glass

Storage

Can be kept for at least 12 months in original unopened packaging.

Store in a cool, frost-free place. Keep out of reach of children.

Health and safety

Wear suitable gloves, protective clothing and safety glasses. If in doubt, always consult the safety data sheet or our R&D department.

Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680

E. info@mavro-int.com

W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2020

All previous editions become invalid upon this publication

Product code: 57949