

# WOOD RENOVATOR

Cleaning agent for cleaning and restoring colour from weathered discoloured wood.



## Product description

Wood Renovator recovers the original colour of grey and weathered wood.

Wood Renovator works quickly, effectively and is biodegradable.

## Use

Wood Renovator can be used outdoors on wooden facade parts, decking, terraces, garden furniture and fences. Can be used on almost all types of wood such as spruce, pine, beech, larch, oak, mahogany and maple.

## Characteristics

- User friendly
- Biodegradable
- Quick and effective on practically all wood types
- Recovers original wood colour
- 100% biodegradable

## Technical data

Odour:	Sharp
Colour:	Light green
Specific weight:	1,00 kg/L
pH:	1 (acidic)
Contains:	Oxalic acid, 2-propylheptanoethoxylate

## Application conditions

Wood Renovator can be applied in all weather conditions. Low temperatures may decrease the efficiency of the product.

## Instructions

1. Always test the product beforehand to test the results and applicability.
2. Apply Wood Renovator undiluted with a low pressure spray, spray bottle or a soft brush.
3. Allow the product to work on the surface for 10-15 minutes and if necessary scrub the surface with a white pad.
4. Rinse the surface thoroughly with warm water under appropriate pressure (For softer wood types lower pressure is recommended to avoid damage).
5. Repeat the procedure if necessary.

## Packaging

1 L

## Consumption

Consumption is 5-10 m<sup>2</sup>/L, depending on the wood type and degree of pollution.

## Practical information

- Do not dilute or mix with other products.
- Corrosive product, always wear gloves and safety goggles.
- Always test the product before use to test the results and applicability.

## Storage

Can be stored for at least 24 months in original unopened packaging. Store in a cool, frost-free place.

## Health and safety

Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. When in doubt, always consult the safety data sheet or our R&D department.



## Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel  
T. +31 418 680 680  
E. [info@mavro-int.com](mailto:info@mavro-int.com)  
W. [www.mavro-int.com](http://www.mavro-int.com)

## Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: January 2024  
All previous editions become invalid upon this publication

Product code: 57330